

Thermal Printer Mechanism Series
With Classic Horizontal Structure

Printer Mechanism

2 Inch
PT48F

World's Best Product

- ▶ Low noise, rugged and durable
- ▶ Printing speed: 90mm/s (8.5V)
- ▶ Easy paper loading



2 Inch Thermal printer mechanism series PT48F

Features

1. Low voltage supply

The voltage used to drive the thermal printer head is equal to the logic voltage, or is driven by a 5V single power line; the range of operating voltage is 8.5V.

2. Compact and lightweight design

The mechanism is compact and light, dimensions: 68.5mm (width) * 36.5mm (depth) * 22.0mm (height).

3. Printing with high resolution

A high-density printer head of 8 dots/mm makes the printing clear and precise

4. High speed printing

According to driving power and sensitivity of thermal paper, set different printing speed required.

Max printing speed is 75 mm/ sec.

5. Easy paper loading

Detachable rubber roller structure makes the paper loading easier

6. Low noise

Thermal line dot printing is used to guarantee low noise printing.



Specifications

Series Model	PT48F	
Print Method	Direct line thermal	
Resolution	8 dots/mm	
Max. Printing Width	48mm	
Number of Dots	384	
Paper width	57.5±0.5mm	
Max. Printing Speed	90mm/s	
Paper Path	Straight	
Drive Voltage	4.2V-9.5V	
PEAK CURRENT	Head(Max.)	3.14A(4.2V/64dots)
	Motor	340mA
RELIABILITY	Pulse Activation	100 million
	Abrasion Resistance	50KM
Operating Temperature	-10 - 50°C	
Dimensions(W*D*H)	68.5*36.5*22.0mm	
Weight	42.9g	
Compatible with	Seiko LTPJ245G	

Applications

- Cash registers
- EFT POS terminals
- Gas pumps
- Portable terminals
- Measuring instruments and analysers
- Taxi meters